


The Best Products, The Best Service...

# SERVICE METAL

ONE CALL GETS IT ALL



## Hex Bushing 150# Malleable Iron Inches / Pounds



| Size          | A    | B    | Approximate Weight (in Pounds) | Hex |
|---------------|------|------|--------------------------------|-----|
| 1/4 x 1/8     | 0.61 | 0.66 | 0.03                           | Out |
| 3/8 x 1/8     | 0.81 | 0.73 | 0.05                           | Out |
| 3/8 x 1/4     | 0.81 | 0.73 | 0.04                           | Out |
| 1/2 x 1/8     | 0.95 | 0.88 | 0.09                           | Out |
| 1/2 x 1/4     | 0.95 | 0.88 | 0.08                           | Out |
| 1/2 x 3/8     | 0.95 | 0.88 | 0.07                           | Out |
| 3/4 x 1/8     | 0.95 | 1.18 | 0.14                           | Out |
| 3/4 x 1/4     | 1.05 | 1.18 | 0.15                           | Out |
| 3/4 x 3/8     | 1.05 | 1.18 | 0.14                           | Out |
| 3/4 x 1/2     | 1.05 | 1.18 | 0.12                           | Out |
| 1 x 1/8       | 1.12 | 1.15 | 0.19                           | In  |
| 1 x 1/4       | 1.12 | 1.15 | 0.19                           | In  |
| 1 x 3/8       | 1.16 | 1.15 | 0.23                           | In  |
| 1 x 1/2       | 1.16 | 1.40 | 0.22                           | Out |
| 1 x 3/4       | 1.18 | 1.40 | 0.18                           | Out |
| 1 1/4 x 1/8   | 1.16 | 1.15 | 0.32                           | In  |
| 1 1/4 x 1/4   | 1.16 | 1.15 | 0.27                           | In  |
| 1 1/4 x 3/8   | 1.20 | 1.15 | 0.25                           | In  |
| 1 1/4 x 1/2   | 1.25 | 1.38 | 0.34                           | In  |
| 1 1/4 x 3/4   | 1.25 | 1.80 | 0.38                           | Out |
| 1 1/4 x 1     | 1.25 | 1.80 | 0.30                           | Out |
| 1 1/2 x 1/8   | 1.30 | 1.18 | 0.45                           | In  |
| 1 1/2 x 1/4   | 1.30 | 1.18 | 0.38                           | In  |
| 1 1/2 x 3/8   | 1.30 | 1.18 | 0.39                           | In  |
| 1 1/2 x 1/2   | 1.30 | 1.40 | 0.42                           | In  |
| 1 1/2 x 3/4   | 1.30 | 1.66 | 0.45                           | In  |
| 1 1/2 x 1     | 1.30 | 1.95 | 0.47                           | Out |
| 1 1/2 x 1 1/4 | 1.30 | 1.95 | 0.31                           | Out |
| 2 x 1/4       | 1.40 | 1.18 | 0.64                           | In  |
| 2 x 3/8       | 1.40 | 1.18 | 0.63                           | In  |
| 2 x 1/2       | 1.50 | 1.37 | 0.55                           | In  |

The Best Products, The Best Service...

# SERVICE METAL

ONE CALL GETS IT ALL



| Size          | A    | B    | Approximate Weight (in Pounds) | Hex |
|---------------|------|------|--------------------------------|-----|
| 2 x 3/4       | 1.50 | 1.68 | 0.60                           | In  |
| 2 x 1         | 1.50 | 1.97 | 0.65                           | In  |
| 2 x 1 1/4     | 1.50 | 2.55 | 0.81                           | Out |
| 2 x 1 1/2     | 1.50 | 2.55 | 0.66                           | Out |
| 2 1/2 x 1/2   | 1.70 | 3.25 | 1.60                           | Out |
| 2 1/2 x 3/4   | 1.58 | 1.65 | 0.82                           | In  |
| 2 1/2 x 1     | 1.58 | 2.00 | 0.90                           | In  |
| 2 1/2 x 1 1/4 | 1.58 | 2.40 | 1.00                           | In  |
| 2 1/2 x 1 1/2 | 1.58 | 2.70 | 1.06                           | In  |
| 2 1/2 x 2     | 1.65 | 3.00 | 0.98                           | Out |
| 3 x 1/2       | 1.88 | 3.80 | 2.10                           | Out |
| 3 x 3/4       | 1.75 | 1.70 | 1.48                           | In  |
| 3 x 1         | 1.70 | 2.00 | 1.44                           | In  |
| 3 x 1 1/4     | 1.70 | 2.40 | 1.40                           | In  |
| 3 x 1 1/2     | 1.70 | 2.70 | 1.44                           | In  |
| 3 x 2         | 1.80 | 3.70 | 2.20                           | Out |
| 3 x 2 1/2     | 1.90 | 3.90 | 1.82                           | Out |
| 3 1/2 x 1 1/2 | 1.75 | 2.75 | 2.10                           | In  |
| 3 1/2 x 2     | 1.94 | 1.80 | 2.16                           | In  |
| 3 1/2 x 2 1/2 | 1.70 | 4.30 | 2.50                           | Out |
| 3 1/2 x 3     | 1.75 | 4.60 | 2.10                           | Out |
| 4 x 1/2       | 2.00 | 4.80 | 4.30                           | Out |
| 4 x 3/4       | 2.00 | 2.00 | 2.30                           | In  |
| 4 x 1         | 1.90 | 2.00 | 2.34                           | In  |
| 4 x 1 1/4     | 1.90 | 2.40 | 2.24                           | In  |
| 4 x 1 1/2     | 1.90 | 2.70 | 2.10                           | In  |
| 4 x 2         | 1.90 | 3.30 | 2.74                           | In  |
| 4 x 2 1/2     | 2.10 | 4.70 | 3.84                           | In  |
| 4 x 3         | 2.10 | 4.70 | 3.20                           | Out |
| 4 x 3 1/2     | 2.33 | 4.75 | 2.92                           | Out |
| 5 x 2         | 2.05 | 3.30 | 4.26                           | In  |
| 5 x 2 1/2     | 2.10 | 4.00 | 4.55                           | In  |
| 5 x 3         | 2.10 | 4.70 | 4.95                           | In  |
| 5 x 4         | 2.10 | 5.80 | 4.36                           | Out |
| 6 x 1 1/2     | 2.20 | 3.35 | 6.74                           | In  |
| 6 x 2         | 2.20 | 3.35 | 6.00                           | In  |
| 6 x 2 1/2     | 2.20 | 3.90 | 6.58                           | In  |
| 6 x 3         | 2.30 | 4.70 | 6.32                           | In  |
| 6 x 4         | 2.30 | 5.90 | 6.78                           | In  |
| 6 x 5         | 2.50 | 7.20 | 7.28                           | Out |

The Best Products, The Best Service...

# SERVICE METAL

ONE CALL GETS IT ALL



| Size  | A    | B    | Approximate Weight<br>(in Pounds) | Hex |
|-------|------|------|-----------------------------------|-----|
| 8 x 6 | 2.75 | 9.00 | 16.40                             | Out |

*\*Malleable Castings conform to ASTM A197*

*\*Hot-Dipped Galvanized Fittings conform to ASTM A153*

*\*Malleable Fitting Dimensions conform to ASME B16.3*

*\*Malleable Bushings, Plugs and Locknuts conform to ASME B16.14*

*\*Malleable Unions conform to ASME B16.39*

*\*NPT Threads on all fittings conform to ASME B1.20.1*

*\*Class 150 fittings are UL listed and FM approved at 300 psi*

*\*Class 300 fittings are UL listed*