


The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL



Bull Head Reducing Tee 150# Malleable Iron Inches / Pounds



Size	A	B	C	Approximate Weight (in Pounds)
1/4 x 1/4 x 3/8	0.90	0.90	0.88	0.20
3/8 x 3/8 x 1/2	1.03	1.03	1.04	0.28
1/2 x 1/2 x 3/4	1.22	1.22	1.20	0.44
1/2 x 1/2 x 1	1.36	1.36	1.26	0.55
3/4 x 1/2 x 1	1.45	1.36	1.37	0.60
3/4 x 3/4 x 1	1.45	1.45	1.37	0.62
3/4 x 3/4 x 1 1/4	1.62	1.62	1.45	0.90
1 x 1 x 1 1/4	1.67	1.67	1.58	0.95
1 x 1 x 1 1/2	1.80	1.80	1.65	1.19
1 x 1 x 2	2.02	2.02	1.73	1.63
1 1/4 x 1 1/4 x 1 1/2	1.88	1.88	1.82	1.45
1 1/4 x 1 1/4 x 2	2.10	2.10	1.90	1.70
1 1/2 x 1 1/4 x 2	2.16	2.10	2.02	1.82
1 1/2 x 1 1/2 x 2	2.16	2.16	2.02	1.86
2 x 2 x 2 1/2	2.60	2.60	2.39	3.50
2 x 2 x 3	2.88	2.88	2.55	4.40
2 1/2 x 2 1/2 x 3	3.00	3.00	2.83	5.82
3 x 3 x 4	3.60	3.60	3.30	8.62

**Malleable Castings conform to ASTM A197*

**Hot-Dipped Galvanized Fittings conform to ASTM A153*

**Malleable Fitting Dimensions conform to ASME B16.3*

**Malleable Bushings, Plugs and Locknuts conform to ASME B16.14*

**Malleable Unions conform to ASME B16.39*

**NPT Threads on all fittings conform to ASME B1.20.1*

**Class 150 fittings are UL listed and FM approved at 300 psi*

**Class 300 fittings are UL listed*