




Reducing 90° Elbows
EXTRA STRONG
Inches / Pounds



Nominal Pipe Size	Outside Diam. of Large End	Inside Diam. of Large End	Wall Thick. at Large End	Outside Diam. of Small End	Inside Diam. of Small End	Wall Thick. at Small End	Center to End (A)	Approximate Weight (in Pounds)
2 x 1	2.375	1.939	0.218	1.315	0.957	0.179	3.00	1.5
2 x 1 ¼	2.375	1.939	0.218	1.660	1.278	0.191	3.00	1.8
2 x 1 ½	2.375	1.939	0.218	1.900	1.500	0.200	3.00	2.0
2 ½ x 1 ¼	2.875	2.323	0.276	1.660	1.278	0.191	3.75	3.3
2 ½ x 1 ½	2.875	2.323	0.276	1.900	1.500	0.200	3.75	3.5
2 ½ x 2	2.875	2.323	0.276	2.375	1.939	0.218	3.75	3.8
3 x 1 ½	3.500	2.900	0.300	1.900	1.500	0.200	4.50	5.0
3 x 2	3.500	2.900	0.300	2.375	1.939	0.218	4.50	5.5
3 x 2 ½	3.500	2.900	0.300	2.875	2.323	0.276	4.50	6.0
3 ½ x 2	4.000	3.364	0.318	2.375	1.939	0.218	5.25	7.0
3 ½ x 2 ½	4.000	3.364	0.318	2.875	2.323	0.276	5.25	7.8
3 ½ x 3	4.000	3.364	0.318	3.500	2.900	0.300	5.25	8.3
4 x 2	4.500	3.826	0.337	2.375	1.939	0.218	6.00	9.3
4 x 2 ½	4.500	3.826	0.337	2.875	2.323	0.276	6.00	10.0
4 x 3	4.500	3.826	0.337	3.500	2.900	0.300	6.00	10.8
4 x 3 ½	4.500	3.826	0.337	4.000	3.364	0.318	6.00	11.5
5 x 2 ½	5.563	4.813	0.375	2.875	2.323	0.276	7.50	15.5
5 x 3	5.563	4.813	0.375	3.500	2.900	0.300	7.50	16.5
5 x 3 ½	5.563	4.813	0.375	4.000	3.364	0.318	7.50	18.0
5 x 4	5.563	4.813	0.375	4.500	3.826	0.337	7.50	19.5
6 x 3	6.625	5.761	0.432	3.500	2.900	0.300	9.00	26
6 x 3 ½	6.625	5.761	0.432	4.000	3.364	0.318	9.00	28
6 x 4	6.625	5.761	0.432	4.500	3.826	0.337	9.00	30
6 x 5	6.625	5.761	0.432	5.563	4.813	0.375	9.00	32
8 x 4	8.625	7.625	0.500	4.500	3.826	0.337	12.00	53
8 x 5	8.625	7.625	0.500	5.563	4.813	0.375	12.00	57
8 x 6	8.625	7.625	0.500	6.625	5.761	0.432	12.00	61
10 x 5	10.750	9.750	0.500	5.563	4.813	0.375	15.00	83
10 x 6	10.750	9.750	0.500	6.625	5.761	0.432	15.00	88
10 x 8	10.750	9.750	0.500	8.625	7.625	0.500	15.00	98
12 x 6	12.750	11.750	0.500	6.625	5.761	0.432	18.00	117
12 x 8	12.750	11.750	0.500	8.625	7.625	0.500	18.00	128
12 x 10	12.750	11.750	0.500	10.750	9.750	0.500	18.00	150



SERVICE METAL
Trust In Every Connection

MASTER DISTRIBUTOR OF
PIPE FITTINGS & VALVES

** Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B.*

